

Micro Processor Based Combination of  
Centre Seal and Side Seal Pouch Making Machine - Mechanical  
(Suitable for laminated film only)



Over 400 Installations in India and abroad



## Micro Processor Based Combination of Centre Seal and Side Seal Pouch Making Machine - Mechanical

### FUNCTIONAL PARAMETERS

PARTICULARS	MODEL		
	CMSV-M - 300	CMSV-M - 400	CMSV-M - 500
<b>Maximum Width of film ( in mm )</b>			
Single Roll	600	800	1000
Two Rolls	300	400	500
<b>Maximum Width of Pouch ( in mm )</b>			
Centre seal	290	390	490
Side seal	300	400	500
<b>Minimum Width of Pouch ( in mm )</b>	50	50	50
<b>Maximum Lenth of Pouch ( in mm )</b>	500*	500*	500*
<b>Minimum Length of Pouch ( in mm )</b>	25	25	25
<b>Maximum Speed of Machine</b>	100-120**	100-120**	100-120**
<b>Electric Heaters</b>			
Centre Seal (W)	600x2	600x2	600x2
Side Seal (W)	600x4	600x4	600x4
Bottom Seal (W)	1000x4	1000x4	1200x4
<b>Connected Load (KW)</b>	10	10	11
<b>Drive</b>			
Main Motor	AC	AC	AC
Draw Motor	AC	AC	AC
Indexing	Servo	Servo	Servo
<b>Size of Machine (in mm)</b>	7000x1500x1800	7000x1600x1800	7000x1700x1800
<b>Weight of the Machine (in Kg)</b>	~2000	~2300	~2600

\* Depends on no. of bottom sealing stations & attachments used.


\*\* Depends on size of pouch & thickness of film.

### Optional Attachments

#### D Punch



#### V Notch



#### Side Flap Insertion



#### Five Side Seal

